ADSORPTION AIR DRYER – Serie NDL

A supply of compressed air is an essential utility for any modern laboratory. Compressed air contains water, oil and dirt which can wear the pneumatic instruments and affect the performance and life time of the analytical instruments. The air dryers are ideal for laboratory use, providing a constant flow of clean, dry compressed air for:

- GC-FID, RMN, AA, ATD, Rheometers, ELSD, Auto Samplers
- Before a zero air generator if the air network is not clean and dry
- Before a nitrogen generator if the air network is not clean and dry

Specyfikacja

RANGE	REFERENCE	FLOW RATE	PURITY	OUTLET PRESSURE
NDL series:	NDL-010	70 L/min	H2O dp -40°C oil < 0,01ppm particles < 1µm	---
	NDL-020	141 L/min		
	NDL-030	283 L/min		
	NDL-040	425 L/min		
	NDL-050	680 L/min		
NDL-3 series:	NDL-2110	300 m3/h	H2O dp -40°C oil < 0,01ppm particles < 1µm	---
	NDL-2120	384 m3/h		
	NDL-3110	450 m3/h		
	NDL-3120	580 m3/h		
	NDL- 3130	740 m3/h		
	NDL-4130	985 m3/h		
	NDL-6120	1152 m3/h		
	NDL-6130	1480 m3/h		

POLYGEN Sp. z o.o. | ul. Portowa 16L/130 | 44-102 Gliwice
Tel.: +48 32 238 81 95 | Biuro: +48 725 725 373 | E-mail: polygen@polygen.com.pl